

CLEANING PROCEDURES

VF-3 Ventless Countertop Fryer



If your Ventless Countertop Fryer looks like the unit on the **left**, use "Cleaning Procedures" spec sheet **PN 96864**



If your Ventless Countertop Fryer looks like the unit on the **right**, use "Cleaning Procedures" spec sheet **PN 92535**

Daily Cleaning Procedures *(see other side for Weekly Cleaning Procedures)*



1 Turn power off, disconnect from main power supply and remove access door. The access door is equipped with lift-off hinges to aid cleaning.



2 Remove food basket and basket lift platform for easy cleaning.



3 Raise element by placing element arm above element retainer and allow oil to drip from it for a few minutes.



4 Carefully remove cooking pot, pour oil through strainer and filter paper or discard used oil properly. The cooking pot can be cleaned in the sink or dishwasher.



5 Remove splash tray for easy cleaning.



6 Clean walls and ceiling of cooking chamber.



WARNING: Rags or paper containing cooking oil can catch fire if exposed to heat. Laundering will not remove the oil. Dispose of all oil-soiled papers and rags in a trash container that is in a ventilated area away from all cooking equipment or other heat sources such as direct sunlight.



CLEANING PROCEDURES

VF-3 Ventless Countertop Fryer



Clean off the element and probe guard.



Completely clean outside panels with non-abrasive stainless steel cleaner and polish. Product door, food basket, lift platform, cooking pot, and splash tray can be removed and placed in the



dishwasher. If using a dishwasher or soap, you will need to neutralize with a vinegar and water solution. There is no need to neutralize when cleaning with Broaster Cooking Well Cleaner (99500).

Weekly Cleaning Procedures



Turn unit off, perform daily cleaning procedures, then soak entire cooking pot overnight in solution of cooking well cleaner (PN 99500) and water.



Before reassembling, lower element to floor of cooking cabinet and remove the grease filter tray.



Remove air filter and clean the grease filter tray and grease filter in the sink or dishwasher. Clean air filter compartment.



Use a screwdriver to remove 3 screws securing probe guard to element box and element spacer. Remove probe guard and clean in sink or dishwasher. Rinse thoroughly and neutralize with vinegar and water before installing back into unit.



Carefully clean any build-up of crumbs on the element and probes behind the probe guard and reinstall the probe guard, grease filter, grease filter tray and air filter. Then raise the element.



Reinstall splash tray. Add fresh oil to cooking pot to the Cold Oil Level Line using the cold oil level indicator. Place the cooking pot in the splash tray, lower the element into the cooking pot. Reinstall lift platform and food basket and the unit is ready to operate.

